

Brand: Genon

Pattern Name: Fuse

Description: Bold circles and lines blend with a gently shaded VUW_[fci bX in FUSE, a geometric ombre tone-on-tone stripe.

Samples of this product can be ordered on-line or can be viewed in the Genon 3 volume binder set

Product Specifications:

Width:	53"- 54"
Type:	II
Weight:	20 ounces/linear yard 620 grams/linear meter 13.3 ounces/square yard
Backing	Recycled poly non-woven
Adhesion of Vinyl to Fabric:	Non-woven supporting materials shall be bonded to the wearing surface. When an attempt is made to pull the wearing surface from the backing by hand, the backing shall delaminate or break before the failure of the bonding.
Breaking Strength (WxF):	135 x 120 Lbs. 600 x 534 Newtons
Tear Strength (WxF) Scale Reading:	41 x 43
Optional Protective Coating(s):	Tedlar® protective finish PreFixx® stain resistant finish

Installation Notes

Match:	Non-reversible straight across match
Horizonal Repeat:	26"
Vertical Repeat:	3"

Fire Rating and Surface Burning Characteristics:

US: Flame Spread 20/ Smoke Developed 115
Fire Rating Class A

Product Features

- Features RECORE™ Recycled Wall Technology
- 30% recycled content
- minimum of 20% post-consumer recycled content
- contributes up to six LEED credits



Limited 5 Year Warranty

MEA Approved, New York Department of Building: Pass

This product contains additives to resist mold and other micro-biological growth on the decorative surface of the product. These additives, however, will not prevent mold growth if moisture is allowed to accumulate in or behind the wall.

Indoor Air Quality:

Low VOC Emitting.

Meets California 01350 Specification for low emissions.

Meets State of Washington Purchase Specification 7 days after installation.

Meets EPA Headquarter Specification 7 days after installation.

GREENGUARD Indoor Air Quality Certified(sm)

