

Caprio

Type II



PHYSICAL PROPERTIES

Width	52/54"	132/137 cm
Total Weight	21.0 oz/lin yd	651 g/lin m
Total Weight	14.0 oz/sq yd	455 g/sq m
Backing	Osnaburg	
Vertical Repeat	22"	56 cm
Horizontal Repeat	13"	33 cm
Construction	Scrim backing	
Min. Weight	15 oz	

PRODUCT SPECIFICATIONS

Caprio as manufactured by Luxes Surfaces, Inc. meets or exceeds G.S.A. Federal Specification CCC-W-408 A/D for Type II wallcovering using test procedures detailed in Federal Specification CCC-T-191-B. The city of New York Department of Building MEA-205-90M has accepted this product for use.

FIRE HAZARD CLASSIFICATION RESULTS

Tested in accordance with ASTM E-84 Tunnel Test
Class "A" Fire Rated

Flame Spread	15
Smoke Developed	5

The assigned numerical rating and other tests referenced in this text are not intended to reflect hazards presented by this or any other material under actual fire conditions.

PRODUCT FEATURES

- * Contains bactericides and mildew inhibitors to protect the products from microbiological and mildew growth
- * 5 Year Warranty Against Manufacturing Defects
- * Environment friendly products that are Cadmium and Mercury Free

INSTALLATION NOTE

Caprio is a non reversible/straight across match

For additional production information please go to www.luxesurfaces.com

Patty Madden ©
All Rights Reserved

Luxe Surfaces, Inc.
501.748.1113
501.978.5694
www.luxesurfaces.com