

A dimensional fabric with post-consumer recycled fiber offering exceptional performance, unmatched fade resistance, and a fire/smoke retardant Class A rating. Made in the U.S.A. from 100% recycled BPA-free plastic drinking bottles and anti-microbial protection, it is lightweight and easy to install and maintain. Soundbite is moisture resistant, mildew, rot and bacteria resistant and is non-allergenic.

- Soundbite Polyester staple fiber high strength fibers which are highly durable and resistant to shrinking and stretching
- 100% recycled content from water & pop bottles; averages 90% post-consumer content
- Easy to clean and maintain
- Fiber does not absorb moisture
- Acoustical qualities
- Velcro compatible, pill resistant
- Soundbite carries the ULC Classification
- Passes NFPA 265 Corner Burn Test (the standard method for evaluating room fire growth contribution of textile wallcovering)
- Solution dyed - Resists sun, fading - high colour fastness to most destructive agents

APPLICATIONS

Designers	Health Care	Hospitality	Corporate	Institutional	Entertainment
<ul style="list-style-type: none"> • Commercial Interiors Market 	<ul style="list-style-type: none"> • Retirement • Nursing Homes • Hospitals • Nursing Stations 	<ul style="list-style-type: none"> • Ballrooms • Conference Rooms • Meeting Rooms 	<ul style="list-style-type: none"> • Executive Conference Rooms • General Offices 	<ul style="list-style-type: none"> • School Auditoriums • Government & Mass Transit Buildings • Day Care Centres 	<ul style="list-style-type: none"> • Theatres • Recreational Centres

ACOUSTICAL PANELS · TACK BOARDS · ELEVATORS · OFFICE PARTITIONS · CHAIR RAILS

FLAMMABILITY SPECIFICATIONS

Applied to 5/8-inch thick Type X gypsum board using Roman PRO-732 Extra Strength Clay Wallcovering Adhesive.

Flame Spread Smoke Developed
10 **50**



Note: The numerical flame spread rating and other test results referenced herein are not intended to reflect hazards presented by this or any other material under actual fire conditions.

Installation and maintenance instructions are enclosed with every Soundbite shipment and should be carefully read prior to installation. For best results, installation is recommended by a qualified textile wallcovering installer.

SPECIFICATIONS

Content	Backing	Weight	Width	Roll Size	Flammability
Recycled Polyester Post-Consumer Solution Dyed	Fused Poly	25 ounces / face weight	63"	12'	EN 15102:2007 + A1:2011 Class A/ASTM E-84

NRC

(ASTM C-423) .20

Fosshield® Antimicrobial Technology - silver & copper ions are incorporated into the polyester fiber and naturally attack microbes. Fosshield® inhibits the growth of bacteria, mold and fungus, providing permanent protection. Ions bind to any microbes that may be present on the fiber and disable their critical functions (metabolism, respirations and reproduction). Typical examples of microbes of common concern are Methicillin-resistant Staphylococcus aureus (MRSA), the Human rhinovirus (common cold), Streptococcus pyogenes (strep), Legionella pneumophila (Legionnaires disease), Human Coronavirus (SARS surrogate), and Feline Calicivirus (Norwalk virus). Fosshield® is the technology incorporated into the FDA cleared SpectraShield® 9500 N95 surgical respirator mask. In the FDA testing, Fosshield® began microbe prevention immediately and eliminated 99.99% of certain odour-causing bacteria after one hour of contact with the respirator surface.

